

Kingspan Inova

Manufacturer	: Kingspan Light + Air (www.kingspanlightandairinternational.com)
Type	: Kingspan Inova
Description	: opening light, controls completely concealed within the construction when closed, suitable for ventilation purposes
Operation	: -24Vdc supply (M24) / - 24Vdc supply + emergency supply batteries (M24FS) / - 24Vdc supply + fire switch (MB24) / - 24Vdc supply + emergency supply batteries + fire switch (MB24FS)
Frame	: thermally separated
Glazing	: to match glass wall construction / single laminated glass (type **) / insulated glass (type **) / sandwich panel (type **); total glazing thickness 6-43mm
Flange sizes (w x l)	: *** x *** mm (identical)
Opening angle	: *** °
Hinge side	: bottom
Installation	: 90° (installation in facades/glass walls)
Aerodynamic flow	: *** m ²
Installation	: installation in glass roof construction / glass wall construction
Protection	: to match glass roof construction / to match glass wall construction / enamel finish with *** layer polyester, layer thickness *** mu, in standard RAL colour (group ***)
Air-tightness	: EN 1026: 600 Pa / EN 12207: class 4
Water tightness	: EN 1027: 600 Pa / EN 12208: class 9a
Resistance to varying load	: EN 12211: 600 Pa (=P2), strength 1800 Pa, EN 12210: class 3
Acoustic values	: 36 dB with insulated glass type 8-20-6.6.2 36 dB with sandwich panel 40 mm
Test	: EN 12101-2
Important	: to satisfy guarantee conditions opening light must be closed automatically during rain and high winds (> 14 m/s). Installation of a rain sensor and wind speed meter is therefore essential.

Kingspan Inova

Manufacturer	: Kingspan Light + Air (www.kingspanlightandairinternational.com)
Type	: Kingspan Inova
Description	: opening light, controls completely concealed within the construction when closed, suitable for ventilation purposes
Operation	: 24Vdc supply (M24) /
Frame	: thermally separated
Glazing	: to match glass wall construction / single laminated glass (type **) / insulated glass (type **) / sandwich panel (type **); total glazing thickness 6-43mm
Flange sizes (w x l)	: *** x *** mm (identical)
Opening angle	: *** °
Hinge side	: top / bottom / side
Installation	: 90° (installation in facades/glass walls)
Aerodynamic flow	: *** m ²
Installation	: installation in glass roof construction / glass wall construction
Protection	: to match glass roof construction / to match glass wall construction / enamel finish with *** polyester layer, layer thickness *** mu, in standard RAL colour (group ***)
Air-tightness	: EN 1026: 600 Pa / EN 12207: class 4
Water tightness	: EN 1027: 600 Pa / EN 12208: class 9a
Resistance to varying load	: EN 12211: 600 Pa (=P2), strength 1800 Pa, EN 12210: class 3
Acoustic values	: 36 dB with insulated glass type 8-20-6.6.2 36 dB with sandwich panel 40 mm
Important	: to satisfy guarantee conditions opening light must be closed automatically during rain and high winds (> 14 m/s). Installation of a rain sensor and wind speed meter is therefore essential.

INTERNATIONAL

Kingspan Light + Air

E: kla.international@kingspan.com

www.kingspanlightandairinternational.com

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.