

Kingspan Lumera

Manufacturer	: Kingspan Light + Air (www.kingspanlightandairinternational.com)
Type	: Kingspan Lumera
Description	: opening light, controls completely concealed within the construction when closed, suitable for ventilation purposes
Operation	: 24Vdc supply (M24)
Frame	: thermally separated
Glazing	: silicone structural -insulated glass (thickness 28 to 37 mm) type **
Flange sizes (w x l)	: *** x *** mm (identical)
Opening angle	: *** °
Hinge side	: bottom
Aerodynamic flow	: *** m ²
Installation	: installation in glass roof construction
Protection	: to match glass roof construction enamel finish with *** polyester layer, layer thickness *** mu, in standard RAL colour (group ***)
Air-tightness	: EN1026: 650 Pa, / EN 12207: class 4
Air leakage	: < 0.1 m ³ /hr/m ² at 50 Pa
Water tightness	: EN1027: 650 Pa / EN 12208: class 4
Resistance to varying Load	: EN 12211: 1500 Pa (=P2), strength 3000 Pa, EN 12210: class E3000
Test	: EN 12101-2
Extra	: trapezium / triangular design possible
Important	: to satisfy guarantee conditions opening light must be closed automatically during rain and high winds (> 14 m/s), except in the event of fire, when the opening light will be required for the extraction of the resulting smoke and heat. Installation of a rain sensor and wind speed meter is therefore essential.

Kingspan Lumera

Manufacturer	: Kingspan Light + Air (www.kingspanlightandairinternational.com)
Type	: Kingspan Lumera
Description	: opening light, controls completely concealed within the construction when closed, suitable for ventilation purposes
Operation	: 24Vdc supply (M24)
Frame	: thermally separated
Glazing	: silicone structural -insulated glass (thickness 28 to 37 mm) type **
Flange sizes (w x l)	: *** x *** mm (identical)
Opening angle	: *** °
Hinge side	: bottom / side
Aerodynamic flow	: *** m ²
Installation	: installation in glass roof construction
Protection	: to match glass roof construction enamel finish with *** polyester layer, layer thickness *** mu, in standard RAL colour (group ***)
Air-tightness	: EN1026: 650 Pa, / EN 12207: class 4
Air leakage	: < 0.1 m ³ /hr/m ² at 50 Pa
Water tightness	: EN1027: 650 Pa / EN 12208: class 4
Resistance to varying Load	: EN 12211: 1500 Pa (=P2), strength 3000 Pa, EN 12210: class E3000
Extra	: trapezium / triangular design possible
Important	: to satisfy guarantee conditions opening light must be closed automatically during rain and high winds (> 14 m/s). Installation of a rain sensor and wind speed meter is therefore essential.

INTERNATIONAL

Kingspan Light + Air

E: kla.international@kingspan.com

www.kingspanlightandairinternational.com

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.