Specification text



Ventilation application

Kingspan Microlab

Manufacturer : Kingspan Light + Air (<u>www.kingspanlightandairinternational.com</u>)

Type : Kingspan Microlab

Description : Continuous natural air extraction. The Microlab labyrinth

construction prevents rain penetration and is specially designed for the continuous extraction of large volumes of air. The system

is designed for use in areas that require the continuous extraction of heat produced during production processes.

Version : single-walled aluminium with straight louvre structure

Closing section : can be supplied with / without closable section. Closable

section equipped with maintenance free bearings and with /

without brushes

Closing mechanism : -double action pneumatic control (P2)

-motor control (24V / 230V)

Flanges : uninsulated

Clear opening (w x l) : *** x *** mm (identical) Flange sizes (w x l) : *** x *** mm (identical)

Effective opening : *** m²

Air passage : $C_{v0} = 0.19$ / $C_{vw} = 0.31$

Application : roof

Installation : on preformed upstand

Protection : -anodised

-enamel finish with *** polyester layer, layer thickness *** mu, in

standard RAL colour (group ***)
-untreated (milled aluminium)

Optional : -sound baffles

-removable side walls for easy cleaning



INTERNATIONAL

Kingspan Light + Air

E: <u>kla.international@kingspan.com</u> <u>www.kingspanlightandairinternational.com</u>

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.

